

Art. No. 103268 tempusFLAT KLETT dB

Ready-to-lay hook-and-loop fastener roll with underlaid footfall sound insulation to accommodate hook-and-loop fastener pipes. For laying on wooden floors, old screeds, tiled floors or flat and smooth concrete surfaces, as well as levelling fills or insulation.

The tempusFLAT KLETT dB system is a composite material consisting of a synthetic fibre top layer of only 2 mm thickness with an extremely strong hook-and-loop fastener effect and 8 mm footfall sound insulation laminated underneath. In combination with the herotec KLETT tubes, as a complete system, it enables the construction of a type A panel heating system according to DIN 18560 and DIN EN 1264. Laying grid of 50 mm and multiples. The tempusFLAT KLETT dB system is installed floating with a self-adhesive overlap on flat surfaces.

Material	synthetic fibre composite material
Colour	grey with black grid
Roll dimensions	8000 x 1300 x 10 mm
Usable dimensions	8000 x 1250 mm
Tolerance	width: ± 2.0 mm, length $\pm 0.1\%$, thickness: $\pm 10\%$
Footfall sound improvement level	up to 28 dB according to DIN 4109-34
Traffic load	4 kN/m ²
Compressibility	≤ 3 mm
Edge formation	self-adhesive strips with release film on the underside of the overlap

