

Art. No. 303046 *tempus*FLAT KLETT

**Ready-to-lay hook-and-loop fastener strip to accommodate hook-and-loop fastener tube, for bonding to insulation laid on site, old screeds, ceramic floor coverings, wooden floors or flat and smooth concrete surfaces.**

Thin-layer Velcro system for panel heating as a special construction with thin-layer screeds or for the construction of panel heating / panel cooling according to DIN 18560 and DIN EN 1264. The system element consists of a synthetic fibre top layer of only 2 mm thickness with a strong hook-and-loop fastener effect when using herotec hook-and-loop fastener tubes.

The adhesive on the reverse side allows fixation on flat surfaces without any further aids. (Substrates according to DIN 18202 with increased requirements).

Material	synthetic fiber (Polyester)
Colour	grey with black imprint
Roll size	1.050 x 20.000 x 2 mm
Screen height	1.000 x 20.000 mm
Tolerance	width: $\pm 2,0$ mm, length $\pm 0,1\%$ , thickness: $\pm 10\%$
Weight per unit area	approx. 300 g/m <sup>2</sup>
Melting point (raw material)	> 110 °C
Bonding	self-adhesive with release film
Edge formation	dull
Laying grid	50 mm und multiples
Pipe diameter	herotec Klett pipe

