

Art. No. 103268 *tempus*FLAT KLETT dB

Ready-to-install Velcro roll with underlaid impact sound insulation to accommodate Velcro pipes. For laying on wooden floors, old screeds, tiled floors or even and smooth concrete ceilings, as well as levelling fills or insulation.

The *tempus*FLAT KLETT dB system is a composite material consisting of a synthetic fibre top layer of only 2 mm thickness with an extremely high bonding effect and the 8 mm impact sound insulation laminated underneath. In combination with the herotec KLETT pipes, as a complete system, it enables the creation of a surface heating system of type A according to DIN 18560 and DIN EN 1264. Installation grid of 50 mm and multiples. The *tempus*FLAT KLETT dB system is laid floating with a self-adhesive overlap on flat surfaces.

Material	Synthetic fibre composite
Color	grey with black grid
Roll dimension	8000 x 1300 x 10 mm
Usable dimension	8000 x 1250 mm
Tolerance	Width: $\pm 2,0$ mm, Length $\pm 0,1\%$, Strength: $\pm 10\%$
Impact sound improvement measure	Up to 28 dB in accordance with DIN 4109-34
Live load	4 kN/m ²
Compressibility	≤ 3 mm
Edge formation	Self-adhesive strip with release film on the underside of the overlap

